



POLYFLEX 101645

SURFACE ACTIVATOR

DESCRIPTION

Polyflex 101645 surface activator is a specially formulated solvent blend designed to activate the membrane surface in order to achieve a better inter-coat adhesion.

FEATURES

- Fast Drying
- Single Component
- Easy to apply

RECOMMENDED USES

- Repair existing membrane
- Overcoat existing membrane
- Incidental patching
- Surface cleaning
- Gun and tool cleaning

TECHNICAL DATA

Color:	Clear liquid	Flash Point:	4.4°C (39.9°F)
Type of Cure:	Evaporation	Shelf life:	1 year
Volatile by volume:	95 - 100	Packaging:	18.93 litres (5 US gallons)
Volatile by Weight:	95 - 100		205 litres (55 US gallons)
Theoretical Coverage of 1 mil:	200-300 ft ² / US gallon		

SURFACE PREPARATION

None required; sanding will improve the inter-coat adhesion

APPLICATION PROCESS

Apply using spray, roller or cotton rag at a rate of 200 to 300 square feet per gallon. Allow the surface activator to dry to touch prior to applying another coat of Polyflex membrane. Remove excess of surface activator with cotton rags.

DISCLAIMER:

"The following is made in lieu of all warranties, expressed or implied: Manufacturer's obligation shall be to replace such quantity of the product proven to be defective. The manufacturer shall not be liable for any injury, loss or damage, direct or incidental or consequential, arising out of the use of or the inability to use the product. Before using, the user shall determine the suitability of the product for the intended use and the user assumes all risk and liability whatsoever in connection therewith. All values shown are approximations. Values indicated are for guide purposes only, as actual values can change due to application conditions, application methods, environmental conditions etc. The information contained herein is subject to change without notice. Consult your representative for a current data sheet. The foregoing may not be altered except by an agreement signed by the officers of the manufacturer." © Polyval Coatings Inc. Polyflex and Polyval are registered trademarks of Polyval Coatings Inc. All Rights Reserved.

Keep in cool and dry area. See the material safety data sheet and product label for complete safety and precaution requirements. Chemical resistance information is currently being updated according to ASTM standards. Please contact your local representative for an update.

Revised 3/7/2013



Polyval Coatings Inc.
520 Boul. Curé Boivin, Boisbriand (Québec) Canada J7G 2A7
TF 1.800.465.0905 | T 450.430.6780 | F 450.430.7877 | polyvalcoatings.com

Disponible en Français